

Intertecnica 6250 LH 3 Point Fastener 92mm-100mm

PART No: IN6250LH-100

FEATURES

Intertecnica 6250 Right Hand 3 Point Fastener with Lock, to suit 92mm - 100mm Panel Thickness

Features:

- Easy-to-use lever action with adjustable strikes provides a positive seal by compressing the gasket along 3 points.
- For overlapping doors.
- European design & Styling
- Stainless Steel lever Handles
- Constructed from Industrial Grade Compositated materials for strength and resistance from corrosion.
- Suitable for both negative & positive temperatures -40/40 °C
- Inside release handle with Photo luminescent arrows
- Invisible & Tamperproof fixings
- Soft & quiet operation
- Lockable
- No reinforcement is needed in the door leaf panel
- Includes luminous internal & external Arrow Labels.
- Max recommended door weight: 100kg
- Door height: 500mm - 3000mm
- Door width: 500mm - 2000mm
- Door panel thickness: 92mm - 100mm
- Door offset: 92mm - 140mm
- Left hand opening.

This Latch kit excludes the Connecting Rod between the latch and strikes.
The manufacturer recommends that a Stainless Steel flat bar 20mm x 3mm thick is used.

Combine this latch set with Intertecnica's IN2830RV Hinge, which offers a non-lift-off hinge and tamper-proof fixings for added security.

CRH & All manufacturers highly recommend that all internal safety release mechanisms fitted to doors are checked at least 3 times weekly to ensure they are functioning correctly.

Colour: Grey

Material: Composite & Stainless Steel



info@crh.com.au

www.crh.com.au