

# Kason C Type Inside Release - Frost free Fibreglass Rod

PART No: K487C

## FEATURES

Frost Free Kason Inside Release Push for 58, 78, 778 Series Latches, up to 150mm thick Panel. See Installation Instructions for cutting lengths dependent on panel thickness .

- Glow in the dark plastic knob for safety.
- Opens padlocked or cylinder K58,78,778 series latches from the inside of a walk-in cold room.
- Furnished with low conduction fibreglass rod for Low Temperature applications.
- Plastic Flange, Fibreglass Rod, Safety-glow Knob.

**Temp Rating:** -40°C to 65°C

**DO NOT use Impact Drivers when fastening the screws as you may crack the ABS material. Hand tighten.**

## ADDITIONAL INFORMATION

There are mandatory safety requirements to protect personnel against entrapment in Refrigerated or Cooling Chambers, Strongrooms or Vaults. Refer to the Technical Information to view the Australian Building Code & Australian/New Zealand Standards. CRH & All manufacturers highly recommend that all internal safety release mechanisms fitted to doors are checked at least 3 times weekly to ensure they are functioning correctly. Suitable for Kason 56 Series Latches. It is highly recommended that low temperature food grade grease is applied in situations where icing may occur (MX6-250)



CRH Australia Pty Ltd 1-3 Nelson Street Moorabbin VIC 3189 Australia t+61 3 9532 f+61 3 9532 2696



[info@crh.com.au](mailto:info@crh.com.au)

[www.crh.com.au](http://www.crh.com.au)