

# 75mm Poly Nylon Wheel Swivel Plate Stainless Steel Castor

PART No: S3382

---

## FEATURES

**Wheel Diameter:** 75mm

**Castor Frame Type:** Swivel

**Wheel Width:** 30mm

**Wheel Type:** Polyurethane

**Wheel Code:** PU3345

**Wheel Bearing Type:** Stainless Steel Ball Bearing

**Castor Height:** 107mm

**Swivel Radius:** 70mm

**Maximum Load Capacity:** 80kg

**Recommended Load Capacity:** 45kg

**Material:** Stainless Steel



## ADDITIONAL INFORMATION

Richmond's Stainless Steel Elite castors are manufactured from Grade 304 stainless steel to provide uncompromised durability when hygiene and health are important, they are highly suited to medical or laboratory equipment. Featuring a stainless steel double ball race swivel head contributing to maintenance free life, fitted with an attractive stainless steel thread guard on the 100 and 125mm or plastic thread guards on the 75mm castors these castors can also be fitted to food carts being constantly moved through cool rooms and steamy kitchens and can be hose cleaned. A full range of round and square pintle options are available through your local Richmond store.

The S3382 from Richmond is a swivel frame castor and features a polyurethane wheel. This swivel castor is in our stainless steel elite plate range and can safely take loads up to 80kg. The S3382 is assembled with stainless steel ball bearings on the castors axle and is mounted with the baseplate. The swivel frame allows full swivel rotation to enable steering. The diameter of the polyurethane wheel is 75mm, the wheel width is 30mm and can be ordered separately (PU3345). To order this castor with a brake, search for S3382B.

