

Fermod Wall Guided Sliding Kit for Doors 2001mm - 2300mm, 115mm - 160mm Thick

PART No: F2156PAN-160

FEATURES

Fermod F2156 Wall Guided Sliding Door Component Kit for Insulated Panel Doors 2001mm - 2300mm Wide, up to 2900mm High x 115mm - 160mm Thick.

Features & Benefits

- Suitable for Frame thicknesses 15mm - 25mm
- Suitable for both positive & negative temperature applications.
- Stylish European design with a pelmet covered rail and 'Drop Down & In' closing system providing the perfect seal with no gasket wear.
- The Wall Guide system is a patented design which takes all components off the floor and does not involve Rollers, Axles or Springs.
- The special design provides impact protection to the door. If the door is heavily impacted it will disengage from the Guide Rail without damage to any components. Any other system in Australia will result in major damage to the door and/or broken components which require a service technician callout. The Fermod system can be put back into operation immediately by anyone with a philips head screw driver.
- Perfect for use in Fast Food, Food Production, Commercial Kitchens, Supermarket & Liquor Store applications.



ADDITIONAL INFORMATION

Weight Rated up to 120kg.

Additional Wall Guide Rail Kits are also available to suit the following door frame thicknesses.

Stock code - **F1157391/36** to suit a 26mm-36mm thick door frame.

Stock code- **F1157391/47** to suit a 37mm-47mm thick door frame.

